

# VST FIELDTRAC 927



**PROJECTOR HEADLAMPS**  
Comes with premium styling and offer greater visibility.



**STAGE 5 COMPLAINT**  
Stage-5 Certified Engine, which complied to latest European Emission Norms.




**NEW BONNET DESIGN**  
Comes with Next Generation Ergonomics for perfect setting of the engine and fresh look.



**MOBILE CHARGING POINT**  
Stay Connected however long your working hours are.



**ENGINE**  
Powerful and Efficient 4 Cylinder Engine.



**TRANSMISSION**  
Comes with 6+2 gear ratio and Side Shift gear lever for varied multiple operations.



**COMFORTABLE AND ADJUSTABLE SEAT**  
European made seat which Offers superior comfort to drivers for long hours of operation.



**POWER STEERING**  
Prevent the wheels from transferring the load to steering column and reduce the driver's Fatigue. Provides more comfort & ease.



**LIFTING CAPACITY**  
Enabled to lift loads up to 500KGS.



# VST FIELDTRAC 927



WWW.IRITRADE.COM

GROW WITH US  
WWW.IRITRADE.COM



# TECHNICAL SPECIFICATION



## ENGINE

Engine HP	25
Emission Norm	Stage 5
Engine Type	Naturally Aspirated, High Torque VST Engine
Max Torque	7.0 kg. m
No. of Cylinders	4
Bore/Stroke (mm)	Ø73 X 78 mm
Displacement (cc)	1306
Rated Speed (RPM)	2700
Air Cleaner	Dry type - Dual filter

## TRANSMISSION

Gear Lever Position	Side Shift
Clutch Type	Single
Clutch Plate Size	Ø 200 mm
Gear Box Type	Sliding mesh
No. of Gear Speeds	6F/2R
Speed Range (km/hr)	Forward : 1.33 - 19.57 Reverse : 1.7 - 7.47
PTO (RPM)	540 & 760
Drive type	4WD

## OTHER FEATURES

Tire Options (Front & Rear Size)	Agriculture (6x12, 8.3x20), Turf (23x8.5-12, 33x15.5-16.5), Industrial (23x8.5-12, 33x15.5-16.5)
----------------------------------	--

Total Tractor Length (mm)	2420
Total Tractor Width (mm)	1085
Wheel Base (mm)	1420
Front wheel track (mm)	890
Rear wheel track (mm)	880
Min. Ground Clearance (mm)	220
Turning Radius with Brakes (m)	2.3
Weight of Tractor without ballast weight (Kg)	835±20
Weight of Tractor with front ballast weight (Kg)	895±20
Driver's Seat	Adjustable, European design Seat

## HYDRAULICS

Hydraulic Type	ADDC
Lifting Capacity (Kg)	600
Three Point Linkage	CAT-I
Rear Spool Valves	2 valves with quick coupling

## ELECTRICALS

Battery Specification	12V, 70AH, 700 cca rating
Head Lamp	4 nos. Projector lamp
Alternator	12V 40 AMP

Steering Type	Hydraulic Assisted Power Steering
Brake Type	Drum brake
Operating Environment	Minus 10 to Plus 45 deg C
Mobile charging point	Yes
Under-hood Silencer	Yes
Battery Cut-off switch	Yes
Front End Loader	Yes
Hood lock with special key	Yes
ROPS	Yes
Drawbar	Yes
Hitch	Yes
Front weights	60 Kg (Standard Fitment)
Rear weights	60 Kg (Optional)

**VST**  
**FIELDTRAC**  
**927**